



UNYTOUCH
MANUFACTURING

Point of Information Kiosk

U09-K190DS-ADC



With an ultra slim, cast metal enclosure, 19" SAW (Surface Acoustic Wave) touch monitor and a powerful Intel Atom base processor, the Unytouch P.O.I Kiosk delivers a cost effective, durable kiosk solution suited to multiple applications.

KEY FEATURES

- 2 piece cast metal enclosure
- 250 cd/m² 19" Display
- 1000:1 contrast ratio display
- Spill resistant IP64 front bezel
- SAW touch sensor
- Intel Atom D525, 1.8Ghz processor, Fanless
- Windows XP Pro included
- HiFi stereo speaker

Brightness
250 cd/m²

Contrast
Ratio
1000:1

Display
Resolution
1280 x 1024

LCD PANEL

| | |
|---------|----------------------------------|
| Chipset | Intel NM10 Express |
| CPU | Intel Atom D525, 1.8 Ghz |
| Memory | 2 GB standard, maximum 4 GB DDR3 |
| HDD | Standard SATA 250 GB |

TOUCH LCD DISPLAY

| | |
|-----------------|--|
| Size/Resolution | 19" TFT LCD / 1280 x 1024 @ 75 Hz |
| Brightness | 250 cd/m ² |
| Touch screen | IP64 Surface Acoustic Wave touchscreen (SAW) |

KIOSK

| | |
|------------------|---|
| Material | Cold rolled steel ST12 SPCC, 3mm tickness or stainless steel, 2mm thickness |
| Color | Flat black |
| Dimension | (H) 168.9 cm x (W) 45.6 cm x (Thickness) 6cm |
| Power | 110V - 220V Power supply |
| Temperature | -5 °C ~ +50 °C |
| LAN | 10/100/1000 |
| I/O Connectivity | 2 x Serial 4 x USB 1 x LPT PS Keyboard & Mouse |
| Speakers | Built-in 2 x 5W speakers & amp |

OPTIONS

| | |
|---------------|---------------------------|
| Floor Plate | Free standing floor plate |
| Packaging | Fumigated wood carton |
| Certification | FCC, CE, UL, ULC, RoHS |
| Warranty | 3 Years |