



U57 SERIES VFD CUSTOMER DISPLAY

The Unytouch U57VFD822 True Flat pole display is black in color, can adjust in height, has a serial cable or USB cable to connect to the host system, and can be used at a checkout to display prices or other messages to customers. The U57VFD dot-matrix display panel can show up to two lines of text, up to 20 characters per line, including commas and decimal points. Customer pole display can be used at a checkout to display prices or other messages to customers. Dot-matrix display panel can show up to two lines of text, with up to 20 characters per line; messages can be programmed and set to scroll automatically. Panel can be rotated and viewing angle can be adjusted for readability. Available in Serial (RS232) and USB Configuration. Attractive Slim True Flat Display.

U57 Series VFD Customer Display

Specifications

U57VFD822S or U57VFD822U VFD Display

- **DISPLAY:** Vacuum Fluorescent Display Blue
- **NUMBER OF CHARACTERS:** 2 X 20 For 5 x 7 dot matrix
- **BRIGHTNESS:** 350~700 cd/m²
- **CHARACTER FONT:** 395 Alphanumeric & 32 International
- **INTERFACE:** RS232 (Serial) or USB
- **CHARACTER SIZE:** 5.25(w) X 9.3(H)
- **DOT SIZE (X*Y):** .85* 1.05mm
- **DIMENSION SMALL:** 8" x 4" x 6" (L x D x H)
- **DIMENSION MEDIUM:** 8" x 4" x 11" (L x D x H)
- **DIMENSION LARGE:** 8" x 4" x 16" (L x D x H)
- **POWER:** 5vDC (USB Powered)
- **COMMAND:** CD5220, Epson POS, Aedex, UTC/S, UTC/C, ADM788, DSP800, EMAX, Logic Control
- **LANGUAGE:** FU.S.A, France, Germany, U.K, DenmarkI, DenmarkII, Sweden, Italy, Japan, Norway, Slavonic, Russia
- **LANGUAGE:** PC437, U.S.A (Standard European)
- **OPERATING HUMIDITY:** 20% ~ 80% RH non-condensing

Options:

- RS232 (Serial) (MFG # U57VFD822S)
- USB (MFG # U57VFD822U)

